









Material and Performance Specification Wire and Rebar Staples

Physical Specifications

Designation	Description	
6 inch Wire Staple*		North American Green 6111 staples are produced from 11 gauge 0.118 to 0.120 bright basic industrial quality 1008/1010 wire, minimum cast, and light oil protection. The staples are generally produced with dimensions of 6 inch (15.2 cm) x 1.0 inch (2.54 cm) x 6.0 inch (15.2 cm) U-shaped configuration.
8 inch Wire Staple		North American Green 6112 staples are produced from 11 gauge 0.118 to 0.120 bright basic industrial quality 1008/1010 wire, minimum cast, and light oil protection. The staples are generally produced with dimensions of 8 inch (20.3 cm) x 2.0 inch (5.0 cm) x 8.0 inch (20.3 cm) U-shaped configuration.
10 inch Wire Staple		North American Green 6102 staples are produced from 8 gauge bright basic industrial quality wire, minimum cast, light oil protection. The staples are generally produced with dimensions of 10 inch (25.4 cm) x 2 inch (5.0 cm) x 10 inch (25.4 cm) U-shaped configuration.
12 inch Wire Staple		North American Green 6122 staples are produced from 8 gauge bright basic industrial quality wire, minimum cast, light oil protection. The staples are generally produced with dimensions of 12 inch (30.5 cm) x 2 inch (5.0 cm) x 12 inch (30.5 cm) U-shaped configuration.
6 inch Circle Top Wire Pin		The 6 inch circle top pins are produced from 11 gauge industrial quality wire, minimum cast, light oil protection. The staples are generally produced with dimensions of 6 inch (15.2 cm) length and 1.5 inch (3.8 cm) diameter circle top configuration. The staples shall be banded in sets of 10.
6 inch V-Top Wire Staple		The 6 inch V-top staples are produced from 11 gauge industrial quality wire, minimum cast, light oil protection. The staples are generally produced with dimensions of 6 inch (15.2 cm) x 1.0 (2.54 cm) x 6 inch (15.2 cm) bent V-shaped configuration.
12 inch Rebar Staple		North American Green 61U12 rebar staples are produced from 3/8 inch steel rebar. The staples are generally produced with dimensions of 12 inch (30.5 cm) x 2 inch (5.0 cm) x 12 inch (30.5 cm) in a U-shaped configuration. The 61U12 rebar staple shall have an approximate weight of 0.75 lbs (0.32 kg).
18 inch Rebar Staple		North American Green 61U18 rebar staples are produced from 3/8 inch steel rebar. The staples are generally produced with dimensions of 18 inch (45.7 cm) x 2 inch (5.0 cm) x 18 inch (45.7 cm) in a U-shaped configuration. The 61U18 rebar staple shall have an approximate weight of 1.13 lbs (0.51 kg).

* Also available in cartridge staples (6111CS), generally produced with 24 6111 staples per cartridge

Proud Participant of:

